

Film	Rev.	Dilution	ASA/ISO	35m	120	Plan	Temp.
ILFORD							
Pan F+50	HC-110	B	50	4	4		20°
Pan F+50	HC-110	E	50	4,30	4,30		20°
Pan 100	HC-110	B	50	6			20°
Pan 100	HC-110	A	100	4			20°
Pan 100	HC-110	B	100	8			20°
Pan 100	HC-110	A	200	5			20°
Pan 100	HC-110	B	200	9			20°
Pan 400	HC-110	A	400	3			20°
Pan 400	HC-110	B	400	6			20°
Pan 400	HC-110	A	800	5			20°
Pan 400	HC-110	B	800	9			20°
Pan 400	HC-110	A	1600	7			20°
Pan 400	HC-110	B	1600	14			20°
FP4+	HC-110	B	50	6	6	6	20°
FP4+	HC-110	A	125	5	5	5	20°
FP4+	HC-110	B	125	8	8	8	20°
FP4+	HC-110	A	200	6	6	6	20°
FP4+	HC-110	B	200	12	12	12	20°
HP5+	HC-110	A	400	3	3	3	20°
HP5+	HC-110	B	400	5	5	5	20°
HP5+	HC-110	A	800	4	4	4	20°
HP5+	HC-110	B	800	10			20°
HP5+	HC-110	B	800	8	8	8	20°
HP5+	HC-110	A	1600	6	6	6	20°
HP5+	HC-110	B	1600	11	11	11	20°
HP5+	HC-110	A	3200	10	10	10	20°
HP5+	HC-110	H	3200	38			20°
Delta 100 Pro	HC-110	B	50	5	5	5	20°
Delta 100 Pro	HC-110	E	50	6	6	6	20°
Delta 100 Pro	HC-110	B	100	6	6	6	20°
Delta 100 Pro	HC-110	E	100	8	8	8	20°
Delta 100 Pro	HC-110	B	200	8	8	8	20°
Delta 100 Pro	HC-110	E	200	10	10	10	20°
Delta 400 Pro	HC-110	B	200	5	5		20°
Delta 400 Pro	HC-110	A	320	4	4		20°
Delta 400 Pro	HC-110	B	400	8	8		20°
Delta 400 Pro	HC-110	A	800	6	6		20°
Delta 400 Pro	HC-110	B	800	10	10		20°
Delta 400 Pro	HC-110	A	1600	8	8		20°
Delta 400 Pro	HC-110	B	1600	14	14		20°
Delta 400 Pro	HC-110	A	3200	13	13		20°
Delta 3200 Pro	HC-110	B	400	6	6		20°
Delta 3200 Pro	HC-110	A	800	5	5		20°

Delta 3200 Pro	HC-110	B	800	8	8		20°
Delta 3200 Pro	HC-110	A	1600	5	5		20°
Delta 3200 Pro	HC-110	B	1600	9	9		20°
Delta 3200 Pro	HC-110	A	3200	8	8		20°
Delta 3200 Pro	HC-110	B	3200	15	15		20°
Delta 3200 Pro	HC-110	A	6400	13	13		20°
SFX 200	HC-110	B	200	9	9		20°
SFX 200	HC-110	B	400	13	13		20°
SFX 200	HC-110	B	800	19	19		20°

KODAK

Tri-X 320	HC-110	B	320			6	20°
Tri-X 400	HC-110	B	200	7	7		20°
Tri-X 400	HC-110	B	200	6	6		20°
Tri-X 400	HC-110	E	200	5	5		20°
Tri-X 400	HC-110	D	250	9	9		20°
Tri-X 400	HC-110	B	320	5	5		20°
Tri-X 400	HC-110	A	400	4	4		20°
Tri-X 400	HC-110	B	400	7.5	7.5		20°
Tri-X 400	HC-110	1+100	400	29	29		20°
Tri-X 400	HC-110	A	800	5,3	5,3		20°
Tri-X 400	HC-110	B	1600	16	16		20°
Tri-X 400	HC-110	1+100	1600	50	50		20°
Tri-X 400	HC-110	1+100	3200	21	21		20°
T-Max 100	HC-110	B	100-200	7	7	8	20°
T-Max 400	HC-110	B	400	6	6	6	20°
T-Max 400	HC-110	B	800	7	7	8	20°
T-Max 400	HC-110	B	1600	9	9		20°

FUJI

Acros 100	HC-110	B	80	4,30	4,30		20°
Acros 100	HC-110	B	100-125	5	5		20°
Acros 100	HC-110	E	100	7	7		20°

FOMA

Fomapan 100	HC-110	B	50	4,30	4,30	4,30	20°
Fomapan 100	HC-110	G	50	13	13	13	20°
Fomapan 100	HC-110	B	100	6	6	6	20°
Fomapan 100	HC-110	F	100	12	12	12	20°
Fomapan 100	HC-110	F	100	8	8	8	20°
Fomapan 100	HC-110	H	100	10	10	10	20°
Fomapan 100	HC-110	H	100	9	9	9	20°
Fomapan 200	HC-110	B	200	3,30	3,30	3,30	20°
Fomapan 200	HC-110	H	200	9	9	12	20°
Fomapan 200	HC-110	H	400	18	18	18	20°
Fomapan 200	HC-110	E	800	11	11	11	20°
Fomapan 400	HC-110	G	200	18	18	18	20°
Fomapan 400	HC-110	E	240	7,30	7,30	7,30	20°
Fomapan 400	HC-110	B	320	6	6	6	20°

Fomapan 400	HC-110	B	400	7	7	7	20°
Fomapan 400	HC-110	H	400	13	13	13	20°
Fomapan 400	HC-110	B	1600	13	13	13	20°
Retropan 320	HC-110	B	320	8		8	20°
Retropan 320	HC-110	B	640	13		13	20°