

Film	Révélateur	Dilution	ISO	35mm	120	Plan film	Temp		
AgfaPhoto APX 100	REV T-MAX	1+4	100	6.5-8			20C		
AgfaPhoto APX 100	REV T-MAX	1+4	200	8.5			20C		
AgfaPhoto APX 400	REV T-MAX	1+4	400	5.5			20C		
AgfaPhoto APX 400	REV T-MAX	1+9	400	10			20C		
AgfaPhoto APX 400	REV T-MAX	1+9	1600	18			20C		
Fomapan 100	REV T-MAX	1+4	100	entre 5 et 6 min	entre 5 et 6 min	entre 5 et 6 min	20C		
Fomapan 100	REV T-MAX	1+9	100	8	8	8	20C		
Fomapan 200	REV T-MAX	1+4	200	entre 5 et 6 min	entre 5 et 6 min	entre 5 et 6 min	20C		
Fomapan 200	REV T-MAX	1+4	400	7.5	7.5	7.5	20C		
Fomapan 400	REV T-MAX	1+4	400	entre 7 et 8 min	entre 7 et 8 min	entre 7 et 8 min	20C		
Fuji Neopan 100 Acros	REV T-MAX	1+4	100	5.5	5.5	5.5	20C		
Fuji Neopan 100 Acros	REV T-MAX	1+4	100	5	5	5	22C		
Fuji Neopan 100 Acros	REV T-MAX	1+9	100	10.5	10.5	10.5	20C		
Fuji Neopan 100 Acros	REV T-MAX	1+4	200	8	8	8	20C		
Fuji Neopan 100 Acros	REV T-MAX	1+4	400	10.5	10.5	10.5	20C		
Fuji Neopan 1600	REV T-MAX	1+9	640	6			24C		
Fuji Neopan 1600	REV T-MAX	1+4	1600	4.5			20C		
Fuji Neopan 1600	REV T-MAX	1+4	3200	10			20C		
Fuji Neopan 400	REV T-MAX	1+4	400	6			6	20C	
Fuji Neopan 400	REV T-MAX	1+9	400	15.25			15.25	20C	
Fuji Neopan 400	REV T-MAX	1+9	640	17			17	20C	
Fuji Neopan 400	REV T-MAX	1+9	640	11			11	24C	
Fuji Neopan 400	REV T-MAX	1+4	800	7.25			7.25	20C	
Fuji Neopan 400	REV T-MAX	1+9	800	19			19	20C	
Fuji Neopan 400	REV T-MAX	1+4	1600	10			10	20C	
Fuji Neopan 400	REV T-MAX	1+4	3200	15			15	20C	
Ilford Delta 100 Pro	REV T-MAX	1+4	50	6			6	6	20C
Ilford Delta 100 Pro	REV T-MAX	1+9	80	12			12	12	24C
Ilford Delta 100 Pro	REV T-MAX	1+4	100	7	7	7	20C		
Ilford Delta 100 Pro	REV T-MAX	1+4	200	8	8	8	20C		
Ilford Delta 3200 Pro	REV T-MAX	1+4	400	5.5	5.5		20C		
Ilford Delta 3200 Pro	REV T-MAX	1+4	800	6.5	6.5		20C		
Ilford Delta 3200 Pro	REV T-MAX	1+4	1250	7	7		20C		
Ilford Delta 3200 Pro	REV T-MAX	1+4	1600	7.5	7.5		20C		
Ilford Delta 3200 Pro	REV T-MAX	1+4	3200	8.5	8.5		20C		
Ilford Delta 3200 Pro	REV T-MAX	1+4	6400	11	11		20C		
Ilford Delta 3200 Pro	REV T-MAX	1+4	12500	14	14		20C		
Ilford Delta 400 Pro	REV T-MAX	1+4	200	5	5		20C		
Ilford Delta 400 Pro	REV T-MAX	1+4	200	4	4		24C		
Ilford Delta 400 Pro	REV T-MAX	1+4	400	6.5	6.5		20C		
Ilford Delta 400 Pro	REV T-MAX	1+4	500	7	7		20C		
Ilford Delta 400 Pro	REV T-MAX	1+4	500	5.5	5.5		24C		
Ilford Delta 400 Pro	REV T-MAX	1+4	800	8.5	8.5		20C		
Ilford Delta 400 Pro	REV T-MAX	1+4	800	7	7		24C		
Ilford Delta 400 Pro	REV T-MAX	1+4	1600	10.5	10.5		20C		
Ilford Delta 400 Pro	REV T-MAX	1+4	1600	8.5	8.5		24C		
Ilford Delta 400 Pro	REV T-MAX	1+4	3200	13.5	13.5		20C		
Ilford Delta 400 Pro	REV T-MAX	1+4	3200	11	11	24C			
Ilford FP4+	REV T-MAX	1+4	100	4.5	4.5	4.5	20C		

Ilford FP4+	REV T-MAX	1+4	100	6	6	6	20C
Ilford FP4+	REV T-MAX	1+4	125	5.5	5.5	5.5	20C
Ilford FP4+	REV T-MAX	1+4	125	8	8	8	20C
Ilford FP4+	REV T-MAX	1+9	160	11	11	11	24C
Ilford FP4+	REV T-MAX	1+4	200	9	9	9	20C
Ilford FP4+	REV T-MAX	1+4	320	12	12	12	20C
Ilford FP4+	REV T-MAX	1+4	400	14	14	14	20C
Ilford HP5+	REV T-MAX	1+4	125	4.5	4.5	4.5	20C
Ilford HP5+	REV T-MAX	1+4	400	6.5	6.5	6.5	20C
Ilford HP5+	REV T-MAX	1+9	400	14	14	14	24C
Ilford HP5+	REV T-MAX	1+9	500	15	15	15	24C
Ilford HP5+	REV T-MAX	1+4	800	8	8	8	20C
Ilford HP5+	REV T-MAX	1+4	1600	9.5	9.5	9.5	20C
Ilford HP5+	REV T-MAX	1+4	3200	11.5	11.5	11.5	20C
Ilford HP5+	REV T-MAX	1+4	3200	9.5	9.5	9.5	24C
Ilford Pan 100	REV T-MAX	1+4	100	8			20C
Ilford Pan 100	REV T-MAX	1+4	200	9			20C
Ilford Pan 100	REV T-MAX	1+4	800	21			21C
Ilford Pan 400	REV T-MAX	1+4	200	5			20C
Ilford Pan 400	REV T-MAX	1+4	400	6			20C
Ilford Pan 400	REV T-MAX	1+4	800	8			20C
Ilford Pan 400	REV T-MAX	1+4	1600	9			20C
Ilford Pan F+	REV T-MAX	1+4	50	4	4		20C
Ilford Pan F+	REV T-MAX	1+9	80	6	6		24C
Ilford Pan F+	REV T-MAX	1+4	125	7	7		20C
Ilford SFX 200	REV T-MAX	1+4	200	8.5	8.5		20C
Ilford SFX 200	REV T-MAX	1+4	400	10.5	10.5		20C
Ilford SFX 200	REV T-MAX	1+4	800	12.5	12.5		20C
Kentmere 100	REV T-MAX	1+4	100	8			20C
Kentmere 400	REV T-MAX	1+4	400	5.5			20C
Kentmere 400	REV T-MAX	1+9	400	10			20C
Kentmere 400	REV T-MAX	1+9	1600	18			20C
Kodak TMax 100	REV T-MAX	1+4	100	7.5	7.5	7.5	20C
Kodak TMax 100	REV T-MAX	1+4	100	6.25	6.25	6.25	24C
Kodak TMax 100	REV T-MAX	1+7	100	9.5	9.5	9.5	24C
Kodak TMax 100	REV T-MAX	1+9	100	17	17	17	20C
Kodak TMax 100	REV T-MAX	1+9	100	13.5	13.5	13.5	24C
Kodak TMax 100	REV T-MAX	1+4	200	7.5	7.5	7.5	20C
Kodak TMax 100	REV T-MAX	1+4	200	6.25	6.25	6.25	24C
Kodak TMax 100	REV T-MAX	1+4	400	10	10	10	24C
Kodak TMax 100	REV T-MAX	1+4	800	11.75	11.75	11.75	24C
Kodak TMax 400	REV T-MAX	1+4	400	6.75	6.75	6.75	20C
Kodak TMax 400	REV T-MAX	1+4	400	5.5	5.5	5.5	24C
Kodak TMax 400	REV T-MAX	1+7	400	12	12	12	20C
Kodak TMax 400	REV T-MAX	1+7	400	8.25	8.25	8.25	24C
Kodak TMax 400	REV T-MAX	1+9	400	25	25	25	18C
Kodak TMax 400	REV T-MAX	1+9	400	20	20	20	20C
Kodak TMax 400	REV T-MAX	1+9	400	13.75	13.75	13.75	24C
Kodak TMax 400	REV T-MAX	1+19	400	36.5	36.5	36.5	20C
Kodak TMax 400	REV T-MAX	1+4	800	6.75	6.75	6.75	20C

Kodak TMax 400	REV T-MAX	1+4	800	5.5	5.5	5.5	24C
Kodak TMax 400	REV T-MAX	1+7	800	8.25	8.25	8.25	24C
Kodak TMax 400	REV T-MAX	1+9	800	13.75	13.75	13.75	24C
Kodak TMax 400	REV T-MAX	1+4	1600	8.5	8.5	8.5	20C
Kodak TMax 400	REV T-MAX	1+4	1600	7.25	7.25	7.25	24C
Kodak TMax 400	REV T-MAX	1+9	1600	13	13	13	28C
Kodak TMax 400	REV T-MAX	1+4	3200	8.25	8.25	8.25	24C
Kodak TMax P3200	REV T-MAX	1+4	400	6			24C
Kodak TMax P3200	REV T-MAX	1+4	400	6.5			24C
Kodak TMax P3200	REV T-MAX	1+4	800	7.5			24C
Kodak TMax P3200	REV T-MAX	1+4	800	6.5			24C
Kodak TMax P3200	REV T-MAX	1+7	800	13			24C
Kodak TMax P3200	REV T-MAX	1+9	800	19.5			24C
Kodak TMax P3200	REV T-MAX	1+9	1280	16			24C
Kodak TMax P3200	REV T-MAX	1+4	1600	10.5			20C
Kodak TMax P3200	REV T-MAX	1+4	1600	7			24C
Kodak TMax P3200	REV T-MAX	1+4	1600	8			24C
Kodak TMax P3200	REV T-MAX	1+4	3200	9.5			24C
Kodak TMax P3200	REV T-MAX	1+4	6400	11			24C
Kodak TMax P3200	REV T-MAX	1+4	12500	12			24C
Kodak TMax P3200	REV T-MAX	1+4	12500	12.5			24C
Kodak TMax P3200	REV T-MAX	1+4	25000	14			24C
Kodak TMax P3200	REV T-MAX	1+4	25000	13.5			24C
Kodak Tri-X 320	REV T-MAX	1+4	320			8	20C
Kodak Tri-X 400	REV T-MAX	1+4	200	5	5		18C
Kodak Tri-X 400	REV T-MAX	1+4	200	6	6		20C
Kodak Tri-X 400	REV T-MAX	1+4	320	7.25	7.25		20C
Kodak Tri-X 400	REV T-MAX	1+4	320	5.25	5.25		24C
Kodak Tri-X 400	REV T-MAX	1+4	400	6	6		20C
Kodak Tri-X 400	REV T-MAX	1+4	400	4.75	4.75		24C
Kodak Tri-X 400	REV T-MAX	1+7	400	7	7		24C
Kodak Tri-X 400	REV T-MAX	1+9	400	10.5	10.5		20C
Kodak Tri-X 400	REV T-MAX	1+9	640	11	11		24C
Kodak Tri-X 400	REV T-MAX	1+4	800	6	6		20C
Kodak Tri-X 400	REV T-MAX	1+4	1000	7.5	7.5		22C
Kodak Tri-X 400	REV T-MAX	1+4	1600	10	8.5		20C
Kodak Tri-X 400	REV T-MAX	1+4	1600	8.75	8.75		20C
Kodak Tri-X 400	REV T-MAX	1+7	1600	11	11		24C
Kodak Tri-X 400	REV T-MAX	1+4	3200	12	11		24C